


Cold Shrinkable

Indoor Termination(26/35 kV)

Product Descriptions

- High quality raw material: High quality liquid silicone rubber is selected as raw material, which has the advantages of reliable insulation performance, excellent electrical performance, pollution resistance, aging resistance, hydrophobicity and cold resistance.
- Advanced equipment and technology: Use advanced equipment for production. The rubber parts produced are free of bubbles, scorch and other impurities. The interface between insulation and semiconductor shielding is well bonded without cracks or peeling.
- Easy to install: Taking advantage of "elastic memory" of rubber and adopting expansion technology, the rubber parts of cable accessory are pre-extended and sleeved into plastic support within the elastic range. When the plastic support is removed during installation, the rubber parts of cable accessories will shrink quickly on the cable.
- Widely use: They are suitable for high altitude, cold, smoke and heavy pollution areas. Especially in flammable and explosive industries such as petroleum, chemical industry and mining.



Technical Requirements

- It can be installed at an angle.
- The connector can be chosen as the compression or sheat bolt.
- The minimum distance from terminal umbrella leaf part to end and to ground is 300mm.
- This product is suitable for XLPE cable with corrugated aluminium sheath and wire shield.
- The earthing system of this product can be braided with tinned copper braided tape or copper wire.
- Applied standard: GB/T 12706.4, IEC 60502.4

Technical Specifications

Area Of Application

Applicable cable cross-sections	50 ~ 630 mm²
Max.system voltage	40.5 kV
System rated frequency	50 Hz
Elevation	≤ 2000 m
Operation temperature	-55 °C~45 °C
Number of cores	1 core, 3 cores
Cable Shield Style	Tape/wire

Design Data

Height	940 mm
Weight of insulator	2.0 ~ 2.7kg
Material of insulator	Liquid silicone rubber
Creepage distance	1015 mm
Storage temperature	0 °C ~ 35 °C
Installation temperature	5 °C ~ 35 °C

Electrical Test (IEC 60502.4)

AC voltage (5 mins)	117 kV
AC voltage (wet, 1 min)	104 kV
Partial discharge test at ambient and elevated temperature	45 kV(≤ 2.8 pC)
Impulse (95 °C ~ 100 °C, 10 impulses of each polarity)	200 kV
AC voltage (after impulse, 15 mins)	65 kV
Humidity	32.5 kV, 300h
Salt fog	32.5 kV, 1000h

Sizing Table

Specification	Applicable cable cross-section(mm ²)	Specification	Applicable cable cross-section(mm ²)
	1 core		3 cores
NLS-1-26/35-50~95	50~95	NLS-3-26/35-50~95	50~95
NLS-1-26/35-120~185	120~185	NLS-3-26/35-120~185	120~185
NLS-1-26/35-240~400	240~400	NLS-3-26/35-240~400	240~400
NLS-1-26/35-500~800	500~800	NLS-3-26/35-500~800	500~800

